

VESTA™ 1000

SDS Preparation Date (mm/dd/yyyy): 01/26/2018

Page 1 of 12

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: VESTA™ 1000

Product Code(s) : None assigned.

Recommended use of the chemical and restrictions on use

: Fuel additive
Use pattern: Professional use only
Recommended restrictions: None known.

Chemical family : Combustion Improver

Name, address, and telephone number of the supplier:

California Fueling

19220 Stare Street
Northridge, CA, U.S.A.
91324

Supplier's Telephone # : 303-618-5310, 8 am-5 pm MST

24 Hr. Emergency Tel # : INFOTRAC: (800) 535-5053 (Within Continental US and Canada); (352)323-3500 (International)

Name, address, and telephone number of the manufacturer:

Refer to supplier

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Clear colorless liquid. Characteristic odor.

Most important hazards: This material is classified as hazardous under OSHA regulations (29CFR 1910.1200) (Hazcom 2012).

Hazard classification:

- Flammable Liquid - Category 4
- Acute toxicity, oral - Category 4
- Acute Toxicity, dermal - Category 4
- Acute toxicity, inhalation - Category 4

Label elements

Hazard pictogram(s)



Signal Word
WARNING!

Hazard statement(s)

- Combustible liquid.
- Harmful if swallowed, in contact with skin or if inhaled.

VESTA™ 1000

SDS Preparation Date (mm/dd/yyyy): 01/26/2018

Page 2 of 12

SAFETY DATA SHEET

Precautionary statement(s)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking.
 Avoid breathing mist or vapor.
 Wash exposed skin thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves and eye/face protection.

If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth.
 IF ON SKIN: Wash with plenty of soap and water. Call a poison center/doctor if you feel unwell. Take off contaminated clothing and wash it before reuse.
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 Call a poison center/doctor if you feel unwell.
 In case of fire: Use water fog, dry chemical, CO2 or 'alcohol' foam to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local regulation.

Other hazards

Other hazards which do not result in classification:

Toxic fumes may be released during a fire. Direct eye contact may cause slight or mild, transient irritation. Direct skin contact may cause slight or mild, transient irritation.

Environmental precautions:

Toxic to aquatic life with long lasting effects. Avoid release to the environment. See Section 12 for more environmental information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Nitric acid, ester	Proprietary	Proprietary	Proprietary

The exact concentrations and/or specific chemical identities of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
- Inhalation* : If inhaled: Remove person to fresh air and keep comfortable for breathing. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Call a poison center/doctor if you feel unwell.
- Skin contact* : IF ON SKIN: Wash with plenty of soap and water. Call a poison center/doctor if you feel unwell. Take off contaminated clothing and wash it before reuse.
- Eye contact* : Immediately flush eye(s) with plenty of water. Flush eyes with running water for at least 5 to 10 minutes. If irritation or symptoms develop, seek medical attention.

VESTA™ 1000

SDS Preparation Date (mm/dd/yyyy): 01/26/2018

Page 3 of 12

SAFETY DATA SHEET

Most important symptoms and effects, both acute and delayed

- : Harmful if swallowed, in contact with skin or if inhaled. May produce symptoms of vasodilation (Reduced blood pressure and other cardiovascular effects to produce such symptoms as throbbing headache, light headedness, flushing, dizziness, weakness, heart palpitations, nausea, fatigue, confusion and possible loss of consciousness). Ingestion of large quantities of nitrates may affect oxygen transport in the blood and blood system, causing methemoglobinemia. Could cause cyanosis (bluish discoloration of the skin due to deficient oxygenation of the blood).
- Direct skin contact may cause slight or mild, transient irritation. Symptoms may include mild redness and swelling.
- Direct eye contact may cause slight or mild, transient irritation. Direct eye contact may cause slight redness.

Indication of any immediate medical attention and special treatment needed

- : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

- : Carbon dioxide (CO₂); Dry chemical; Alcohol resistant foam; Water fog

Unsuitable extinguishing media

- : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Combustible liquid. May be ignited by open flame. Toxic fumes may be released during a fire. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable Liquid - Category 4

Hazardous combustion products

- : Nitrogen oxides; Carbon oxides

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

- : Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures

- : Avoid breathing mist or vapor. Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

- : Prevent product from entering drains, sewers, waterways and soil. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.

VESTA™ 1000

SDS Preparation Date (mm/dd/yyyy): 01/26/2018

Page 4 of 12

SAFETY DATA SHEET

Methods and material for containment and cleaning up

- : Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Do not use combustible absorbents, such as sawdust. Contact the proper local authorities.

Special spill response procedures

- : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).
 US CERCLA Reportable quantity (RQ): None.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

- : Wear suitable protective equipment during handling. Wear protective gloves and eye/face protection. Use only outdoors or in a well-ventilated area. Avoid breathing mist or vapor. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking. Ground all equipment during handling. Keep away from incompatibles. Keep containers tightly closed when not in use. Wash thoroughly after handling. Empty containers retain residue (liquid and/or vapor) and can be dangerous. Do not cut, weld, drill or grind on or near this container.

Conditions for safe storage

- : Store in a cool, dry, well ventilated area, away from incompatibles. Inspect periodically for damage or leaks. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. No smoking. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area. Maximum storage temperature: 40°C (104°F).
 Unsuitable materials for containers Natural Rubber; Butyl rubber

Incompatible materials

- : Oxidizing agents; Strong bases; Strong acids; Reducing agents

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Exposure Limits:</u>				
<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Nitric acid, ester	N/Av	N/Av	N/Av	N/Av

Exposure controls

Ventilation and engineering measures

- : Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection

- : If airborne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02. Advice should be sought from respiratory protection specialists.

Skin protection

- : Wear protective gloves/clothing. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

VESTA™ 1000

SDS Preparation Date (mm/dd/yyyy): 01/26/2018

Page 5 of 12

SAFETY DATA SHEET

- Eye / face protection** : Wear eye/face protection. Wear safety glasses with side shields (or goggles). A full face shield may also be necessary.
- Other protective equipment** : Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.
- General hygiene considerations** : Avoid breathing mist or vapors. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance** : Clear colorless liquid.
- Odor** : Characteristic odor.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting/Freezing point** : Not available.
- Initial boiling point and boiling range** : Not available.
- Flash point** : 78°C (172.4°F)
- Flashpoint (Method)** : Pensky Martens Closed Cup
- Evaporation rate (BuAe = 1)** : Not available.
- Flammability (solid, gas)** : Not applicable.
- Lower flammable limit (% by vol.)** : 0.25%
- Upper flammable limit (% by vol.)** : Not available.
- Oxidizing properties** : None known.
- Explosive properties** : Not explosive
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Relative density / Specific gravity** : 0.96 - 0.97
- Solubility in water** : slightly soluble (12.6 mg/L)
- Other solubility(ies)** : Soluble in: Hydrocarbons; Methanol; Chlorinated solvents
- Partition coefficient: n-octanol/water or Coefficient of water/oil distribution** : 5.24
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : 130°C
- Viscosity** : 1.7 - 1.8 cSt @ 20°C (68°F)
- Volatiles (% by weight)** : No data available.
- Volatile organic Compounds (VOC's)** : Not available.
- Absolute pressure of container** : Not applicable.
- Flame projection length** : Not applicable.
- Other physical/chemical comments** : No additional information.

SECTION 10. STABILITY AND REACTIVITY

- Reactivity** : Not normally reactive.

VESTA™ 1000

SDS Preparation Date (mm/dd/yyyy): 01/26/2018

Page 6 of 12

SAFETY DATA SHEET

- Chemical stability** : Stable under normal conditions.
- Possibility of hazardous reactions** :
 : Temperatures above 100°C (212°F) may cause self-accelerating exothermic decomposition which causes a rapid rise in temperature and pressure.
 Thermal-ignition critical temperatures (Tc) and reaction times (t) at Tc + 1°C:
 - Cylindrical metallic drum diameter 400 mm: Tc = 93 °C (199 °F); t = 27 hours.
 - Cylindrical metallic container diameter 2 m: Tc = 65 °C (149 °F); t = 6 days.
 - Cylindrical metallic container diameter 10 m: Tc = 38 °C (100 °F); t = 30,5 days.
- Conditions to avoid** : Open flames, sparks, high heat, direct sunlight, and close proximity to incompatible substances. Do not use in areas without adequate ventilation. Avoid contact with incompatible materials.
- Incompatible materials** : Oxidizing agents; Strong acids; Strong bases; Reducing agents
- Hazardous decomposition products** : None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

- Routes of entry inhalation** : YES
- Routes of entry skin & eye** : YES
- Routes of entry Ingestion** : YES
- Routes of exposure skin absorption** : YES

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

- : Harmful if inhaled. Inhalation of high concentrations of vapors, may cause respiratory irritation. Symptoms may include sore throat, running nose and shortness of breath. May produce symptoms of vasodilation (Reduced blood pressure and other cardiovascular effects to produce such symptoms as throbbing headache, light headedness, flushing, dizziness, weakness, heart palpitations, nausea, fatigue, confusion and possible loss of consciousness).

Sign and symptoms ingestion

- : Harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Ingestion may cause symptoms similar to inhalation. Ingestion of large quantities of nitrates may affect oxygen transport in the blood and blood system, causing methemoglobinemia. Could cause cyanosis (bluish discoloration of the skin due to deficient oxygenation of the blood).

Sign and symptoms skin

- : Direct skin contact may cause slight or mild, transient irritation. Symptoms may include mild redness and swelling. May be absorbed and cause symptoms similar to those for inhalation.

Sign and symptoms eyes

- : Direct eye contact may cause slight or mild, transient irritation. Direct eye contact may cause slight redness.

Potential Chronic Health Effects

- : Frequent or prolonged contact may dry the skin, leading to discomfort and dermatitis.

Mutagenicity

- : Not expected to be mutagenic in humans. No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

- : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

- : This product is not expected to cause reproductive or developmental effects.

VESTA™ 1000

SDS Preparation Date (mm/dd/yyyy): 01/26/2018

Page 7 of 12

SAFETY DATA SHEET

Sensitization to material : Not expected to be a skin or respiratory sensitizer.
Specific target organ effects : According to the classification criteria of U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012), this product is not expected to cause target organ toxicity through single or repeated exposures.

Medical conditions aggravated by overexposure : Pre-existing skin, eye, respiratory or blood system disorders.

Synergistic materials : No information available.

Toxicological data : This material is classified as hazardous under OSHA regulations (29CFR 1910.1200) (Hazcom 2012). Hazardous classification:
Acute toxicity - Category 4. Harmful if swallowed, in contact with skin or if inhaled. Based on Human Evidence).

See below for toxicological data on the substance.

<u>Chemical name</u>	LC₅₀ (4hr)	LD₅₀	
	<u>inh, rat</u>	<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Nitric acid, ester	> 4.6 mg/L (mist) (rabbit)	> 9600 mg/kg (rat)	> 4800 mg/kg (rabbit)

Other important toxicological hazards : None reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity : Toxic to aquatic life with long lasting effects. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

See the following tables for the substance's ecotoxicity data.

Ecotoxicity data:

<u>Ingredients</u>	CAS No	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
Nitric acid, ester	Proprietary	2 mg/L (Zebra fish)	N/Av	None.

<u>Ingredients</u>	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
Nitric acid, ester	Proprietary	> 12.6 mg/L (Daphnia magna)	N/Av	None.

<u>Ingredients</u>	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
Nitric acid, ester	Proprietary	3.22 mg/L/72hr (Green algae)	12.6 mg/L/72hr	None.

Persistence and degradability : Not expected to be rapidly biodegradable.

VESTA™ 1000

SDS Preparation Date (mm/dd/yyyy): 01/26/2018

Page 8 of 12

SAFETY DATA SHEET

Bioaccumulation potential : Not expected to bioaccumulate. See the following data for ingredient information.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
Nitric acid, ester (CAS Proprietary)	5.24	N/Av

Mobility in soil : No data is available on the product itself.

Other Adverse Environmental effects

: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal : Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.
 Empty containers retain residue (liquid and/or vapor) and can be dangerous. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Methods of Disposal : Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.








VESTA™ 1000

SDS Preparation Date (mm/dd/yyyy): 01/26/2018

Page 9 of 12

SAFETY DATA SHEET

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
The following 49CFR/DOT information applies to shipments in bulk packagings (> 450 L / 119 gallons):					
49CFR/DOT	NA1993	Combustible liquid, n.o.s. (2-Ethylhexyl nitrate)	Combustible.	III	 
49CFR/DOT Additional information	The 'label' appearing here is the placard to be used for bulk shipments. This product contains marine pollutants. When shipped in bulk packagings (> 450 L / 119 gallons), or by sea, this material must be identified as a Marine pollutant according to 49 CFR sections 172.203 (I) and 172.322. "Marine pollutant" must be included with the shipping description on documentation.				
The following 49CFR/DOT information applies to shipments in non-bulk packagings (≤ 450 L / 119 gallons):					
49CFR/DOT	None.	Not regulated.	not regulated	none	
49CFR/DOT Additional information	Not regulated for road or rail shipment if packaged in non-bulk containers (450 L / 119 Gallons or less each). If shipping non-bulk containers by sea, refer to IMDG shipping information.				
TDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-Ethylhexyl nitrate)	9	III	 
TDG Additional information	This material may be shipped as an exempted marine pollutant in accordance with TDG Section 1.45.1 and Special Provision 99.				
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-Ethylhexyl nitrate)	9	III	 
IMDG Additional information	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass. The environmentally hazardous substance mark must appear on packagings holding more than 5 litres of the material.				

Special precautions for user : Appropriate advice on safety must accompany the package. Keep away from heat, sparks and open flame. - No smoking.

Environmental hazards : This product meets the criteria for an environmentally hazardous material according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: This information is not available.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

<u>Ingredients</u>	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
Nitric acid, ester	Proprietary	Yes	None.	None.	No	N/Ap

VESTA™ 1000

SDS Preparation Date (mm/dd/yyyy): 01/26/2018

Page 10 of 12

SAFETY DATA SHEET

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes:

Physical hazards (Flammable liquid)

Health hazards (Acute toxicity)

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Nitric acid, ester	Proprietary	No	N/Ap	No	No	No	No	No	No

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	CAS #	European EINECS	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
Nitric acid, ester	Proprietary	Proprietary	Listed	Listed	Listed	Listed	Listed	Listed

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists
 AICS: Australian Inventory of Chemical Substances
 ATE: Acute Toxicity Estimate
 CA: California
 CAS: Chemical Abstract Services
 CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
 CFR: Code of Federal Regulations
 CSA: Canadian Standards Association
 DOT: Department of Transportation
 ECHA: European Chemicals Agency
 ECOTOX: U.S. EPA Ecotoxicology Database
 EINECS: European Inventory of Existing Commercial chemical Substances
 ENCS: Existing and New Chemical Substances
 EPA: Environmental Protection Agency
 HSDB: Hazardous Substances Data Bank
 IARC: International Agency for Research on Cancer
 IBC: Intermediate Bulk Container
 IECSC: Inventory of Existing Chemical Substances
 IMDG: International Maritime Dangerous Goods
 IOC: Inventory of Chemicals
 IUCLID: International Uniform Chemical Information Database
 KECI: Korean Existing Chemicals Inventory
 KECL: Korean Existing Chemicals List

VESTA™ 1000

SDS Preparation Date (mm/dd/yyyy): 01/26/2018

Page 11 of 12

SAFETY DATA SHEET

LC: Lethal Concentration
 LD: Lethal Dose
 MA: Massachusetts
 MN: Minnesota
 N/Ap: Not Applicable
 N/Av: Not Available
 NIOSH: National Institute of Occupational Safety and Health
 NJ: New Jersey
 NOEC: No observable effect concentration
 NTP: National Toxicology Program
 OECD: Organisation for Economic Co-operation and Development
 OSHA: Occupational Safety and Health Administration
 PA: Pennsylvania
 PEL: Permissible exposure limit
 PICCS: Philippine Inventory of Chemicals and Chemical Substances
 RCRA: Resource Conservation and Recovery Act
 RI: Rhode Island
 RTECS: Registry of Toxic Effects of Chemical Substances
 SARA: Superfund Amendments and Reauthorization Act
 SDS: Safety Data Sheet / Material Safety Data Sheet
 STEL: Short Term Exposure Limit
 TDG: Canadian Transportation of Dangerous Goods Act & Regulations
 TLV: Threshold Limit Values
 TSCA: Toxic Substance Control Act
 TWA: Time Weighted Average
 WHMIS: Workplace Hazardous Materials Identification System

References



- : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2017.
- 2. International Agency for Research on Cancer Monographs, searched 2017.
- 3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2017 (Chempodium, HSDB and RTECs).
- 4. Material Safety Data Sheets from manufacturer.
- 5. US EPA Title III List of Lists - March 2015 version.
- 6. California Proposition 65 List - December 15, 2017 version.
- 7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2017.

Preparation Date (mm/dd/yyyy)

: 01/26/2018

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

<p><u>Prepared for:</u> California Fueling 19220 Stare Street Northridge, CA, U.S.A., 91324 Telephone: (303) 618-5310 Direct all enquiries to: California Fueling</p>	
<p><u>Prepared by:</u> ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.); (888) 977-4834 (Canada) http://www.thecompliancecenter.com</p>	



VESTA™ 1000

SDS Preparation Date (mm/dd/yyyy): 01/26/2018

Page 12 of 12

SAFETY DATA SHEET

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by California Fueling and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and California Fueling expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this Safety Data Sheet does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and California Fueling.

END OF DOCUMENT